

ARMONIA LED

Pendant LED luminaire



Mounting:	Suspended on 1,5m long steel chain suspension
Body material:	Steel and aluminium
Colour:	Standard Black 9005, other RAL colours on request (please add RAL code after index number)
LED module:	Philips / Osram or Tridonic LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard
Driver:	Electronic driver or electronic integrated, DALI on request
Emergency unit:	On request
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20 in standard, IP44 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	Aluminium white
Light distribution:	Symmetric

General data: 5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
With integrated AC driver								
5286.1100/830	1100	10	3000	Ra > 80	50.000	5	3	5,50
5286.1100/840	1100	10	4000	Ra > 80	50.000	5	3	5,50
5286.2000/830	2000	18	3000	Ra > 80	50.000	5	3	5,50
5286.2000/840	2000	18	4000	Ra > 80	50.000	5	3	5,50
5286.3000/830	3000	27	3000	Ra > 80	50.000	5	3	5,50
5286.3000/840	3000	27	4000	Ra > 80	50.000	5	3	5,50
With AC/DC driver								
3457.1100/830	1100	12	3000	Ra > 80	50.000	5	3	6,10
3457.1100/840	1100	12	4000	Ra > 80	50.000	5	3	6,10
3457.2000/830	2000	20	3000	Ra > 80	50.000	5	3	6,10
3457.2000/840	2000	20	4000	Ra > 80	50.000	5	3	6,10
3457.3200/830	3200	31	3000	Ra > 80	50.000	5	3	6,10
3457.3200/840	3200	31	4000	Ra > 80	50.000	5	3	6,10

