

Wall mounted

number)

request N/A

N/A

N/A

N/A

IP20

N/A

Symmetric

0°C ... +40°C

220-240V 50/60Hz

Direct / indirect lighting

Steel and aluminium

LED GU10 retrofit lamp included

2700K , 3000K or 4000K available

>80 in standard, other on

Standard Black / Orange, other RAL colours on request (please add RAL code after index

NOBO 60 WAF LED





$IP20 \xrightarrow[3040Hz]{226340Hz} \overleftarrow{F} \textcircled{=} \textbf{CE}$	
--	--

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5381.710/827	710	9,2	2700	Ra > 80	15.000	3	4	1,70
5381.740/830	740	9,2	3000	Ra > 80	15.000	3	4	1,70
5381.780/840	780	9,2	4000	Ra > 80	15.000	3	4	1,70

Wall mounted LED luminaire.

Mounting: Body material:

Colour:

LED module:

Driver:

Colour temperature:

Colour Rendering Index (CRI):

Emergency unit:

Movement sensor: Daylight control sensor:

Operating temperature

range:

IP Class: Power:

Lighting direction:

Reflector type:

Light distribution:

General data:

3 Years standard warranty Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

