

## NOBO 100 STF LED

Free standing floor luminaire



<b>Mounting:</b>	Free standing
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Black / Orange, other RAL colours on request ( please add RAL code after index number )
<b>LED module:</b>	LED GU10 retrofit lamp included
<b>Colour temperature:</b>	2700K , 3000K or 4000K available
<b>Colour Rendering Index (CRI)</b>	>80 in standard, other on request
<b>Driver:</b>	N/A
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C... +40°C
<b>IP Class:</b>	IP20 in standard, IP44 on request
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct / indirect lighting
<b>Reflector type:</b>	N/A
<b>Light distribution:</b>	Symmetric
<b>General data:</b>	3 Years standard warranty Different lumen output or wattage available on request All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%. System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5370.710/827	710	9,2	2700	Ra > 80	15.000	3	4	11,00
5370.740/830	740	9,2	3000	Ra > 80	15.000	3	4	11,00
5370.780/840	780	9,2	4000	Ra > 80	15.000	3	4	11,00

