

NOBO 60 LED

Pendant LED luminaire



Mounting:	Suspended on 1,5m long steel wire suspension (with wire length control)
Body material:	Steel and aluminium
Colour:	Standard Black / Orange, other RAL colours on request (please add RAL code after index number)
LED module:	LED GU10 retrofit lamp included
Colour temperature:	2700K , 3000K or 4000K available
Colour Rendering Index (CRI):	>80 in standard, other on request
Driver:	N/A
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	N/A
Light distribution:	Symmetric
General data:	3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5359.710/827	710	9,2	2700	Ra > 80	15.000	3	4	1,90
5359.740/830	740	9,2	3000	Ra > 80	15.000	3	4	1,90
5359.780/840	780	9,2	4000	Ra > 80	15.000	3	4	1,90

